SELECT Blue 1.74 MR-174

Available coatings: UC / HMC+

Finished | Power Range | Minus SPH

UV420 | Made in China

Coatings listed for minus powers. Plus-power coatings subject to confirmation.

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
-1.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.25	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.50	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.75	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.25	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.50	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.75	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.25	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.50	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.75	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.25	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.50	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.75	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.25	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.50	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.75	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.00	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.25	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.50	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.75	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.00	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.25	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.50	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.75	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.00	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.25	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.50	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.75	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.00	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.25	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

Only the documented minus supply range is shown.

Plus geometry on later pages does not establish plus availability.

SELECT Blue 1.74 MR-174

Available coatings: UC / HMC+

Finished | Power Range | Minus SPH | continued

UV420 | Made in China

Coatings listed for minus powers. Plus-power coatings subject to confirmation.

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
-9.50	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.75	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-10.00	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-10.25	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-10.50	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-10.75	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-11.00	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-11.25	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-11.50	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-11.75	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-12.00	B	B	B	B	B	B	B	B	B	C	C	C	C	C	C	C	C
-12.25	B	B	B	B	B	B	B	B	B	C	C	C	C	A	A	A	A
-12.50	B	B	B	B	B	B	B	B	B	C	C	C	C	A	A	A	A
-12.75	B	B	B	B	B	B	B	B	B	C	C	C	C	A	A	A	A
-13.00	B	B	B	B	B	B	B	B	B	C	C	C	C	A	A	A	A
-13.25	B	C	C	C	C	C	C	C	C	A	A	A	A	A	A	A	A
-13.50	B	C	C	C	C	C	C	C	C	A	A	A	A	A	A	A	A
-13.75	B	C	C	C	C	C	C	C	C	A	A	A	A	A	A	A	A
-14.00	B	C	C	C	C	C	C	C	C	A	A	A	A	A	A	A	A
-14.25	B	C	C	C	C	A	A	A	A	A	A	A	A				
-14.50	B	C	C	C	C	A	A	A	A	A	A	A	A				
-14.75	B	C	C	C	C	A	A	A	A	A	A	A	A				
-15.00	B	C	C	C	C	A	A	A	A	A	A	A	A				
-15.25	A	A	A	A	A	A	A	A	A								
-15.50	A	A	A	A	A	A	A	A	A								
-15.75	A	A	A	A	A	A	A	A	A								
-16.00	A	A	A	A	A	A	A	A	A								
-16.25	A	A	A	A	A												
-16.50	A	A	A	A	A												
-16.75	A	A	A	A	A												
-17.00	A	A	A	A	A												
-17.25	A																
-17.50	A																
-17.75	A																
-18.00	A																

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

Only the documented minus supply range is shown.

Plus geometry on later pages does not establish plus availability.

SELECT Blue 1.74 MR-174

Finished | AS

MR-174 | UV420 | Made in China

CYL (- ON -) See Power Range					POWER	CYL (+ ON -) See Power Range				
DIA-(mm)	C/T (mm)	E/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA-(mm)
75	2	2	4.366	4.366	PLANO					
	1.8	2	4.366	4.116	0.25					
	1.6	2.1	4.366	3.866	0.5					
	1.5	2.3	4.366	3.616	0.75					
	1.4	2.3	4.366	3.366	1					
	1.3	2.4	4.366	3.116	1.25					
	1.2	2.5	4.366	2.866	1.5					
	1.1	2.6	4.366	2.616	1.75					
	1	2.9	5.145	3.145	2					
	1	3.1	5.145	2.895	2.25					
	1	3.3	5.145	2.645	2.5					
	1	3.5	5.145	2.395	2.75					
	1	3.7	5.381	2.381	3	5.45	2.63	2.96	1	65
	1	4	5.381	2.131	3.25	5.7		3.18		
	1	4.2	5.381	1.881	3.5	5.96		3.31		
	1	4.4	5.868	2.118	3.75	6.13		3.44		
	1	4.7	5.868	1.868	4	6.45		3.58		
	1	4.8	5.868	1.618	4.25	6.12	2.1	3.87		
	1	5.2	6.327	1.827	4.5	6.4		3.93		
	1	5.4	6.327	1.577	4.75	6.67		4.11		
	1	5.7	6.327	1.327	5	6.87		4.26		
	1	5.9	6.563	1.313	5.25	6.62	1.62	4.4		
	1	6.1	6.563	1.063	5.5	6.84		4.58		
	1	6.3	6.786	1.036	5.75	7.07		4.78		
	1	6.6	6.786	0.786	6	7.34		4.96		
70	1	6.2	7.509	1.259	6.25	6.98	1.1	5.15		
	1	6.5	7.509	1.009	6.5	7.3		5.44		
	1	6.6	7.509	0.759	6.75	7.47		5.63		
	1	6.8	8.246	1.246	7	7.71		5.76		
	1	7.1	8.246	0.996	7.25	8		5.91		
	1	7.3	8.246	0.746	7.5	8.23		6.06		
	1	7.6	8.733	0.983	7.75	8.49		6.16		
	1	7.8	8.733	0.733	8	8.64		6.35		
	1	8.1	8.733	0.483	8.25	8.94		6.55		
	1	8.3	9.484	0.984	8.5	9.27		6.74		
	1	8.5	9.484	0.734	8.75	9.35		6.86		
	1	8.7	9.484	0.484	9	9.56		7.01		
	1	9	9.901	0.651	9.25	9.86		7.14		
	1	9.2	9.901	0.401	9.5	10.03		7.33		
	1	9.5	10.374	0.624	9.75	10.26		7.48		
	1	9.7	10.374	0.374	10	10.46		7.62		
65	1	8.64	10.878	0.6	10.25	10.73		7.76		
	1	8.8	11.128	0.6	10.5	10.91		7.89		
	1	9	11.381	0.6	10.75	11.14		8.09		
	1	9.3	11.631	0.6	11	11.38		8.17		
	1	9.51	11.883	0.6	11.25	11.56		8.38		
	1	9.7	12.133	0.6	11.5	11.74		8.46		

SELECT Blue 1.74 MR-174

Finished | AS

MR-174 | UV420 | Made in China

CYL (- ON -) See Power Range					POWER	CYL (+ ON -) See Power Range				
DIA-(mm)	C/T (mm)	E/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA-(mm)
65	1	10	12.386	0.6	11.75	11.98	1.1	8.55	1	65
	1	10.2	12.636	0.6	12	12.2		8.74		
	1	10.4	12.888	0.6	12.25					
	1	10.7	13.138	0.6	12.5					
	1	10.9	13.391	0.6	12.75					
	1	11.2	13.641	0.6	13		Centre thickness tolerance range: 1.0 -0.1/+0.3 mm			
	1	11.43	13.894	0.6	13.25					
	1	11.6	14.144	0.6	13.5					
	1	11.94	14.382	0.6	13.75					
	1	12.2	14.632	0.6	14					
	1	12.5	14.885	0.6	14.25					
	1	12.7	15.135	0.6	14.5					
	1	12.99	15.388	0.6	14.75					
	1	13.3	15.638	0.6	15					
	1	14	16.17	0.83	15.25					
	1	14.2	16.17	0.63	15.5					
	1	14.5	16.65	0.83	15.75					
	1	14.7	16.65	0.63	16					
	1	15.2	17.18	0.89	16.25					
	1	15.4	17.18	0.63	16.5					
	1	16	17.7	0.89	16.75					
	1	16.2	17.7	0.63	17					
	1	16.6	18.17	0.89	17.25					
	1	16.8	18.17	0.72	17.5					
	1	17.4	18.7	0.91	17.75					
	1	17.6	18.7	0.69	18					
70	1	9.8	11.13	0.8	10.25					
	1	10	11.08	0.56	10.5					
	1	10.3	11.62	0.85	10.75					
	1	10.6	11.57	0.52	11					
	1	10.9	12.07	0.8	11.25					
	1	11.2	12.11	0.53	11.5					
	1	11.5	12.6	0.8	11.75					
	1	11.8	12.59	0.5	12					
	1	12.1	13.13	0.83	12.25					
	1	12.4	13.11	0.58	12.5					
	1	12.7	13.69	0.85	12.75					
	1	13	13.64	0.58	13					
	1	13.3	14.18	0.88	13.25					
	1	13.6	14.09	0.58	13.5					
	1	13.9	14.63	0.84	13.75					
	1	14.2	14.62	0.57	14					
	1	14.6	15.16	0.83	14.25					
	1	14.9	15.13	0.55	14.5					
	1	15.3	15.67	0.86	14.75					
	1	15.6	15.65	0.62	15					