SELECT IMPACT Blue 1.60 MR-8 Plus

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV420 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
0.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-0.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-0.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-0.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-1.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-1.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-1.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-1.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-2.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-2.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-2.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-2.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-3.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-3.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-3.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-3.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-4.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-4.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-4.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-4.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-5.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-5.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-5.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-5.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

A: Ø65 mm

B: Ø70 mm

C: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT IMPACT Blue 1.60 MR-8 Plus

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV420 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
+0.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+0.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+0.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A: Ø65 mm

B: Ø70 mm

C: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT IMPACT Blue 1.60 MR-8 Plus

Finished | AS | Ø65 / 70 / 75 mm

UV420 | Made in China

Technical index: 1.597

CYL(-ON-) -0.25~-4.00					POWER	CYL(+ON-) -0.25~-4.00				
DIA (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA (mm)
Ø75	2	2	4.25	4.25	PLANO					
	2.3	1.8		4	0.25	3.75	3.5	2.1	1.9	Ø70
	2.5	1.7		3.75	0.5	4		2.2	1.6	
	2.6	1.6		3.5	0.75	4.25		1.8	1.4	
	2.9	1.6		3.25	1	4.5		1.9	1.4	
	3.1	1.5	4.25	3	1.25	4.75		2	1.1	
	3.4	1.4		2.75	1.5	5		2.2		
	3.4	1.15		2.5	1.75	5.25		2.5		
	3.6	1.15		2.25	2	5.5		2.7		
Ø75	4	1.15	5.25	3	2.25	4.75	2.5	2.7		Ø65
	4.2			2.75	2.5	5		2.9		
	4.3			2.5	2.75	5.25		3.1		
	4.6			2.25	3	5.5		3.3		
	4.7			2	3.25	5.75		3.6		
	5.2			1.75	3.5	6		3.8		
	5.5			1.5	3.75	6.25		4		
	5.8			1.25	4	6.5		4.3		
Ø75	6.2		6.25	2	4.25	5.25	1	4.3		
	6.4			1.75	4.5	5.5		4.6		
	6.7			1.5	4.75	5.75		4.8		
	7			1.25	5	6		5.1		
	7.4			1	5.25	6.25		5.3		
	7.7			0.75	5.5	6.5		5.5		
	7.9			0.5	5.75	6.75		5.7		
	8.2			0.25	6	7		5.9		
Ø70 CYL -0.25 to -4.00	7.9	1.15	8.25	2	6.25	**1. "MINUS" LENS** 1. SPH Axis : -0.00 ~ -6.00 CYL Axis : -0.25 ~ -4.00 2. SPH Axis: -6.25 ~ -10.00 CYL Axis : -0.25 ~ -4.00 **2. "PLUS" LENS** SPH Axis : +0.25 ~ +6.00 CYL Axis : -0.25 ~ -4.00 **3. TOLERANCE (+/- 0. 3 mm)** CENTER- EDGE THICKNESS				
	8.2			1.75	6.5					
	8.3			1.5	6.75					
	8.5			1.25	7					
	8.8			1	7.25					
	9.1			0.75	7.5					
	9.3			0.5	7.75					
	9.6			0.25	8					
	10.2		9.25	1	8.25					
	10.5			0.75	8.5					
	10.6			0.5	8.75					
	10.9			0.25	9					
	11.4		10	0.75	9.25					
	11.6			0.5	9.5					
	11.9			0.25	9.75					
	12.3			0	10					